

■ Calgary ☎ 403-248-8837 ■ Edmonton ☎ 780-435-2800 ■ London ☎ 519-672-5561 ■ Moncton ☎ 506-384-6101  
■ Montreal ☎ 450-655-6676 ■ Ottawa ☎ 613-741-4591 ■ Quebec ☎ 418-681-878801 ■ Saskatoon ☎ 306-651-2647  
■ Toronto ☎ 905-760-8211 ■ Vancouver ☎ 604-522-3944 ■ Winnipeg ☎ 204-694-2849

## MAMMOUTH SOPRAMASTIC ALU

**Description:** SOPRAMASTIC ALU is a solvent-based mastic containing SBS synthetic rubber and bitumen. It complements bituminous waterproofing membranes and is used as jointing mastic, caulking material and joint filler. It is compatible with bituminous materials and ensures good waterproofing.

SOPRAMASTIC ALU contains leafing aluminium pigmentation providing superior protection against ultraviolet light and its high level of polymer ensures long-term flexibility and elasticity.

**Application:** SOPRAMASTIC ALU must be applied to clean, sound substrates.

The 310 ml cartridges can be used with a standard cartridge extruder.

Excellent adherence on most materials without primer.

**Can be applied to damp surfaces.** To optimise its reflective properties, avoid contact of water until SOPRAMASTIC ALU is dry.

### Properties:

SOPRAMASTIC ALU meets the requirements of CAN/CGSB-37.5-M89 and ASTM D4586 standards.

Properties	SOPRAMASTIC ALU
Specific gravity at 20°C (kg/l)	1.22
Colour	Aluminium
Application Temperature Range (°C)	-10 to 35 (14 to 95 °F)
Service Temperature Range (°C)	-40 to 80 (-40 to 175 °F)
Solids by Weight (%)	85
Flash point (ASTM D-93)	28°C (82°F)
Drying time	Between 4 and 24 hours, depending on temperature and quantity applied.

(All values are nominal)

**Packaging:** 310 mL cartridges (20 per box).

Shelf life: Up to 12 months in original sealed containers, in cool and ventilated area.

**Cleaning:** Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

**Precautions:** SOPRAMASTIC ALU is a flammable product. Store in a cool, dry area.

**CONSULT THE MATERIAL SAFETY DATA SHEET PRIOR TO USE.**



**NOTE:** SOPREMA INC. may modify the composition and/or utilisation of its products without prior notice. Consequently orders will be filled according to the latest specification.