



SOPREMA Inc.  
Technical Services  
1688 Jean-Berchmans-Michaud  
Drummondville (Quebec) J2C 8E9  
Telephone : 1-877-MAMMOUTH  
Web Site : www.soprema.ca

## TECHNICAL BULLETIN

NO.: **0209CE**  
DATE ISSUED: October 2009  
REPLACES: N/A

Relates to: 07 27 00 Air Barriers

### Subject: Securock wall sheathing from CGC

#### Related subjects: Air/Vapour Barrier

The following bulletin has been prepared in order to clarify Soprema's position regarding the use of Sopraseal Stick 1100T self-adhesive air/vapour barrier membrane in conjunction with Securock wall sheathing from CGC.

Securock wall sheathing is an acceptable support for Sopraseal Stick 1100T self-adhesive membranes. Securock wall sheathing surface must be primed with ELASTOCOL STICK primer prior to membrane's installation.

SOPREMA general recommendations regarding surface preparation and membrane installation (including temperature limitations) apply to these boards and remain unchanged.

SOPREMA does not recommend any other method of application on these boards. Also, to achieve the best application possible, it is important to follow the manufacturer's recommendations for the delivery, storage and handling of these boards.

This bulletin covers all summer grade Sopraseal Stick 1100T membranes as well as Sopraseal Stick 1100T winter grade membranes manufactured after September 21, 2009.

- END OF TECHNICAL BULLETIN -

**Note:** This technical bulletin was prepared by SOPREMA Inc. for architects, engineers, building owners, and contractors, as a reference guide in designing, selecting and constructing roofing, and/or waterproofing and/or air/vapour barriers utilizing SOPREMA Inc. products. SOPREMA Inc. reserves the right to change, or modify, at our discretion, without prior notice, any information, recommendations, or specifications contained in this technical bulletin.